

partybag Mini

PARTYBAG MINI TECHNICAL SPECIFICATIONS

ACOUSTICAL:

Frequency response (-3dB):	100 Hz ÷ 20000 Hz
Max SPL:	112 dB
Tweeter:	0.75" with ferrofluid (Power handling 25 W RMS)
Woofer:	4" by FaitalPRO® (Power handling 30 W RMS)
Amplifier:	Class D 2x25 W RMS, DSP controlled
Enclosure:	Plywood, with bass-reflex

INPUT/OUTPUT:

Analog inputs:	Mini-jack 3.5 mm stereo with selectable MIC/LINE level
Digital inputs:	MP3/USB Player, <i>Bluetooth</i> ® receiver
Analog outputs:	Mini-jack 3.5 mm
Mini-jack MIC/LINE sensitivity:	30 mV/300 mV (-32 dBv/- 10 dBv)
Maximum input level:	1 V (0 dBv)
Maximum output level:	1 V (0 dBv)

ELECTRICAL:

USB charging port:	5 V \equiv 500 mA
Battery:	4 cell (14.8 V) Li-Ion 2600 mAh (38.5 Wh)
Battery range at full volume:	4 hours
Battery range at mid volume:	16 hours
External power supply:	Input 100-240 V \sim 50/60 Hz 0.5 A, Output 16.8 V \equiv 1 A

MECHANICAL:

Height:	48 cm
Width:	30 cm
Depth:	20 cm
Net weight:	2.4 Kg
Woofer protection:	Plastic mesh grid, black
Backpack internal volume:	16 liters
Backpack fabric:	CORDURA®/Polyester, handcrafted in Italy